

BRYSTON



BRYSTON T¹⁰ SPEAKER BROCHURE

WELCOME TO THE NEXT LEVEL

BYSTON



BYSTON LOUDSPEAKERS

RULE NUMBER ONE

Unless you live in an open field the way your speaker will perform is a function of the ROOM/SPEAKER interface. The standing waves, the nearby surface reflections, the tonal balance and the soundstage are all greatly affected by placement of the speaker within the confines of the listening room.

Bryston speakers are designed to consider that all speakers are listened to in real rooms and the interaction of the room with the speaker with specific designs can be made to enhance the listening experience. This is accomplished by de- signing speakers which have the widest 'smooth and even' on and off axis frequency response over the widest angle possible both vertically and horizontally as much as current technology will permit.

RULE NUMBER TWO

It's very important to choose the correct size speaker for your listening room. A small speaker in a large room will not pressurize the room properly and a large speaker in a small room will typically over drive your room. There is some flexibility with this rule when you take into account the polar response of a given speaker, Point Source vs Vertical Array, vs Planar etc.

In days past Bryston's loudspeaker engineers participated in ground breaking research that modernized speaker engineering. Since then, we have done more to correlate measured performance with perceived sound quality than just about every other manufacturer on the planet.

Bryston's loudspeakers are extraordinary in their ability to reproduce lifelike sounds both accurate in timbre and dynamic range. Further, they are protected by our industry leading 10 Year Warranty against defects in materials and workmanship. Dressed in our stock or custom real wood veneer or paint, they look as great as they sound. Contact your local dealer today for an audition.

SOUND POWER

We perfect the entire power response of the loudspeaker. We don't just hear the direct on-axis frequency response. Bryston loudspeakers have a flat response from ± 15 degrees off axis. Furthermore, the entire 360 degree sound-field demonstrates exceptional freedom from major peaks or dips that could color the reflected sound around your room. Therefore, Bryston loudspeakers are far easier to place in your room than competing brands and will sound more neutral overall.

REAL WORLD DYNAMICS

Sounds in real life are dynamic - they can move from whisper quiet to dramatically loud in a split second. For speakers to sound real, they need to respond just as fast. Bryston speakers can keep up with whatever your music and movie sound-tracks throw at them. The largest Model T¹⁰ can play at up to 118dB before it even starts to distort! Even the smallest Tiny T¹⁰ can exceed 100dB all without deviating from the ideal response curve taken at reference level. It's not uncommon to find speakers costing many times as much that can't compete.



BYSTON



WHEN YOU LISTEN
TO A SPEAKER
IN A ROOM
YOU ARE NOT
LISTENING TO THE
'ON AXIS'
RESPONSE
YOU ARE
LISTENING TO THE
'SOUND POWER'


DEFY
THE
ORDINARY

BYSTON LOUDSPEAKERS

STEREO OR CINEMA

Truly great loudspeakers are equally comfortable playing music or movies. They show no bias. Our Model T and Model A Series are nuanced and delicate when playing fingerpicked guitar but also powerful and in command when rocking out. They have been engineered to have no character of their own. Let your music and movies do the talking. Hear them just as the artists intended through Bryston Loudspeakers.


DIRECT VS REFLECTED



When you are listening to a loudspeaker in a room you are listening to a balance between the 'Direct Sound' and the 'Reflected Sound' from the boundaries of the room – this is called the 'Power Response or Sound Power'.

Typically the measurements that you see show the on-axis response of the speaker at one meter. In fact we do not hear that direct measurement independently. We hear a mixture of all the 'on-axis' and all the reflected 'off-axis' sound (sound power) in the listening room.

FAMILY OF CURVES



Bryston speakers utilize anechoic measurements and blind listening tests in designing our speakers. We call this our 'FAMILY OF CURVES.'

The family of curves is made up of amplitude response measurements taken in a sphere around the speaker in an anechoic environment.

The performance you hear in your room is a summation of this family of curves in varying degrees of weighting. In the design of each Bryston speaker we begin with anywhere from 120 to 300 measurements depending on the size of the speaker. From there each curve is considered both individually and as groups with particular algorithms applied to each curve in the group and then each group against the whole.

From this collection of measurements we published the Bryston Listening Window and Sound Power curves for each product.


BRYSTON




**THIS LACK
OF
DYNAMIC
COMPRESSION
IS ASTONISHING
PERFORMANCE
REGARDLESS
OF PRICE**



A. B. C's. OF BRYSTON LOUDSPEAKERS



More useful than a single on-axis frequency response plot is that of the listening window - an average of measurements taken on and off axis. Note the superb linearity and absence of major peaks and dips that cause audible tonal errors. Sound power is a weighted average of the speaker's total radiated energy. Excellent linearity here coincides with superb sound-staging and remarkable balance in the room



Dynamic compression, or the inability to maintain composure under high playback levels plagues many loudspeakers. Bryston's astonishing lack of compression brings a lifelike realism to dynamic events in music and movie soundtracks without introducing artifacts that might disrupt your enjoyment. Note that the frequency response of the speaker at a punishing 110dB is virtually identical to that of the speaker at a more common level of 90dB. This is astonishing performance regardless of price

A. Extraordinary dynamic range and lack of compression has been achieved by developing drivers that are efficient, capable of high power handling and extraordinarily low levels of distortion. We also use multiple drive units in parallel so that the system can play louder with less effort than a single driver solution.


B. Essential to the clarity and neutrality of our speakers are well engineered crossover networks. Whether internal (standard) or external (Signature Edition), these not only divide the full spectrum of sound across different drivers, but also are used to correct even small non-linearities found in our driver elements.

C. Thick walls, up to a 1½ inch thick front baffle, and a precisely designed network of internal braces ensure that the cabinet is all but perfectly inert and contributes virtually no sonic signature of its own. With no cabinet resonances, you only hear the beautiful sound of your recordings.

D. Thorough understanding of fluid dynamics led us to develop a fluted port profile which eliminates vent noise even at extreme pressures. This mastery of engineering enabled us to utilize the advantages of a vented system without the turbulent distortion frequently associated with ports.

E. Bryston carefully engineered drivers to achieve excellent performance and reliability parameters using advanced modeling and finite element analysis tools. Once initially developed, we verified performance and durability in our factory anechoic chamber.

BRYSTON



**A TRUE
POINT SOURCE
SPEAKER IS
PHYSICALLY
IMPOSSIBLE
FROM A PURE
PHYSICS
STANDPOINT**




BRYSTON MODEL TINY T-10 POINT SOURCE

In physics, a point source is an energy source with negligible dimensions – a tiny, singular point in space where the energy emanates. In physics terms, a true point source speaker would be infinitely small with the ability to produce frequencies from 20Hz to 20kHz.

Most speakers approximate this performance by using single drivers or coax drivers or in most cases 2 or 3-way drivers clustered together as close as physically possible.

A point source speaker's sound expands away from the speaker as an ever-enlarging sphere.

Unlike the line array system or an omni a point source speaker radiates sound in a spherical pattern.



SPECIFICATIONS:

Enclosure Reflex / Vortex

Max Amp RMS Wattage 250 Watts

Min Amp Power 10 Watts

Freq Resp +/-3dB 60 Hz- 20 kHz

Impedance (Ohms) 8

SPL in Room 1w/1m (dB) 91 dB

SPL Anechoic 1w/1m (dB) 87 dB

X-Over 250 Hz & 2.4 kHz

Tweeter Single 1" Titanium

Midrange Single 3"

Woofer Single 6.5"

Dimensions H W D (inches) 15.5x8.5x8.25

Dimensions H W D (cm) 48x23x26

Weight (lbs) each 11

Weight (kg) each 5



TINY T¹⁰

BRYSTON



ENGINEERED

**FOR
MUSIC**



BRYSTON MODEL COMPACT T-10 POINT SOURCE

SPECIFICATIONS:

Enclosure Reflex / Vortex
Max Amp RMS Wattage 500 Watts
Min Amp Power 10 Watts
Freq Resp +/-3dB (Hz) 45 Hz-20 kHz
Impedance (Ohms) 8
SPL in Room 1w/1m 91 dB
SPL Anechoic 1w/1m 87 dB
X-Over 250 Hz & 2 kHz
Tweeter Single 1" Titanium
Midrange Single 5.25"
Woofer Single HP 6.5"
Dimensions H W D (inches) 19x9.3x10.5
Dimensions H W D (cm) 48x23x26
Weight (lbs) each 26
Weight (kg) each 12



COMPACT T¹⁰

BRYSTON MODEL MINI T-10 POINT SOURCE

SPECIFICATIONS:

Enclosure Reflex / Vortex
Max Amp RMS Wattage 600 Watts
Min Amp Power 20 Watts
Freq Resp +/-3dB 35 Hz- 20 kHz
Impedance (Ohms) 4
SPL in Room 1w/1m 90 dB
SPL Anechoic 1w/1m 86 dB X-Over
250 Hz & 2 kHz
Tweeter Single 1" Titanium
Midrange Single 5.25"
Woofer Single 8"
Dimensions H W D (inches)
22.5 x 10.5 x 10
Dimensions H W D (cm)
57x26 x25
Weight (lbs) each 42
Weight (kg) each 19



MINI T¹⁰

BRYSTON



**ENGINEERED
FOR
MUSIC**




THE PERFECT COMBO

COMPACT T10 & TS-10 SUB

SPECIFICATIONS:

Enclosure Reflex / Vortex
Max Amp RMS Wattage 500 Watts
Min Amp Power 10 Watts
Freq Resp +/-3dB (Hz) 45 Hz-20 kHz
Impedance (Ohms) 8
SPL in Room 1w/1m 91 dB
SPL Anechoic 1w/1m 87 dB
X-Over 250 Hz & 2 kHz
Tweeter Single 1" Titanium
Midrange Single 5.25"
Woofer Single HP 6.5"
Dimensions H W D (inches) 19x9.3x10.5
Dimensions H W D (cm) 48x23x26
Weight (lbs) each 26
Weight (kg) each 12



COMPACT T₁₀

BRYSTON MODEL COMPACT TS-10 SUB

SPECIFICATIONS:

Enclosure Sealed
RMS Wattage 600 Watts Internal
Freq Resp +/-3dB 25 Hz- 150 kHz
Crossover Hz 40/60/80/100/150
Phase adjustment 0-180
Inputs RCA/XLR/Hi-Level
Outputs RCA/XLR
Woofer Dual 8"
Dimensions H W D (inches) 24x10.5x16.8
Dimensions H W D (cm) 61x27x43
Weight (lbs) each 89
Weight (kg) each 40



COMPACT TS₁₀ SUB

BRYSTON




WELCOME
TO THE
NEXT LEVEL


BRYSTON PARTIAL LINE ARRAY

Bryston tower speakers are 'partial' Line Arrays and different from point source speakers in the way they radiate energy into the room.

The sound radiates outward in an expanding cylinder, as though from a line in space.




POINT SOURCE



LINE ARRAY

There are some significant advantages to this type of sound propagation:

- More uniform SPL throughout the listening space
- Arrays effectively reduce cancellations in floor and ceiling reflections
- The perceived volume is quite uniform throughout the listening area.
- Having the woofers pressurizing the room at four different locations also assist in reducing the huge dips and peaks in the frequency response all too common in most listening rooms.
- Allows you to hear more of the music in your room.
- Superior Intelligibility
- A greater Sense of Realism



BRYSTON



**MUSIC
WITH
EMOTION**

BRYSTON MODEL TRIM T¹⁰ LINE ARRAY



TRIM T¹⁰

SPECIFICATIONS:

Enclosure Reflex / Vortex
Max Amp RMS Wattage 700 Watts
Min Amp Power 30 Watts
Freq Resp +/-3dB 32 Hz- 20 kHz
Impedance (Ohms) 4
SPL in Room 1w/1m 91 dB
SPL Anechoic 1w/1m 87 dB
X-Over 250 Hz & 2 kHz

Tweeter Dual 1" Titanium
Midrange Dual 5.25"
Woofer Dual HP 6.5"
Dimensions H W D (inches) 60x10x16
Dimensions H W D (cm) 152x26x41
Weight (lbs) each 83
Weight (kg) each 38





THE
DEMO
IS
EVERYTHING

BRYSTON MODEL MIDDLE T¹⁰ LINE ARRAY



MIDDLE T¹⁰

SPECIFICATIONS:

Enclosure Reflex / Vortex
Max Amp RMS Wattage 1000 Watts
Min Amp Power 50 Watts
Freq Resp +/-3dB 28 Hz - 20 kHz
Impedance (Ohms) 4
SPL in Room 1w/1m 92 dB
SPL Anechoic 1w/1m 88 dB
X-Over 250 Hz & 2 kHz

Tweeter Dual 1" Titanium
Midrange Dual 5.25"
Woofer Quad HP 6.5"
Dimensions H W D (inches) 67x10x17
Dimensions H W D (cm) 170x44x26
Weight (lbs) each 102
Weight (kg) each 46

BRYSTON



**BECAUSE
YOU'RE
TIRED OF
LISTENING
TO
AVERAGE**

BRYSTON MODEL T¹⁰ LINE ARRAY



MODEL T-10

SPECIFICATIONS:

Enclosure Reflex / Vortex
Max RMS Amp Wattage 1200 Watts
Min Amp Power 50 Watts
Freq Resp +/-3dB 25 Hz- 20 kHz
Impedance (Ohms) 4
SPL in Room 1w/1m 92 dB
SPL Anechoic 1w/1m 88 dB

X-Over 250 Hz & 2 kHz
Tweeter Dual 1"
Midrange Dual 5.25"
Woofer Quad 8"
Dimensions H W D (inches) 72x12x17
Dimensions H W D (cm) 183x31x44
Weight (lbs) each 133
Weight (kg) each 61



BRYSTON



BRYSTON T¹⁰ CENTER SPEAKERS



MODEL TC¹⁰ CENTER

SPECIFICATIONS:

Enclosure Acoustic Suspension
Max RMS Amp Wattage 1200 Watts
Min Amp Power 50 Watts
Freq Resp +/-3dB 30 Hz- 20 kHz
Impedance (Ohms) 4
SPL in Room 1w/1m 92
SPL Anechoic 1w/1m 88 dB
X-Over 250 Hz & 2 kHz

Tweeter Dual 1" Titanium
Midrange Dual 5.25"
Woofer Dual 8"
Dimensions H W D (inches)
11"x40"x17"
Dimensions H W D (cm)
27x101x42
Weight (lbs) each 108
Weight (kg) each 49



MIDDLE / TRIM TC¹⁰ CENTER

SPECIFICATIONS:

Enclosure Acoustic Suspension Max
Amp RMS Wattage 1000 Watts
Min Amp Power 50 Watts
Freq Resp +/-3dB 35 Hz - 20 kHz
Impedance (Ohms) 4
SPL in Room 1w/1m 92 dB
SPL Anechoic 1w/1m 88 dB
X-Over 250 Hz & 2 kHz

Tweeter Dual 1" Titanium
Midrange Dual 5.25"
Woofer Dual HP 6.5"
Dimensions H W D (inches) 10x40x17
Dimensions H W D (cm) 27x100x42
Weight (lbs.) each 90
Weight (kg) each 41

BRYSTON



BRYSTON T¹⁰ CENTER SPEAKERS



MODEL COMPACT TC¹⁰ CENTER

SPECIFICATIONS:

Enclosure Acoustic Suspension
Max RMS Amp Wattage 500 Watts
Min Amp Power 10 Watts
Freq Resp +/-3dB (Hz) 54 - 20kHz
Impedance (Ohms) 8 Ohms
SPL in Room 1w/1m(db) 91 dB

SPL Anechoic 1w/1m(db) 87 dB
X-Over 300 Hz & 2.4 kHz
Tweeter Single 1"
Midrange Single 5.25"
Woofer Dual 6.5"
Dimensions H W D (inches) 11.5x21x13.9
Dimensions H W D (mm) 292x530x352



MODEL TINY TC¹⁰ CENTER

SPECIFICATIONS:

Enclosure Acoustic Suspension
Max RMS Amp Wattage 250 Watts
Min Amp Power 10 Watts
Freq Resp +/-3dB (Hz) 75 - 20k
Impedance (Ohms) 8
SPL in Room 1w/1m(db) 90 dB

SPL Anechoic 1w/1m(db) 86 dB
X-Over 2.7 kHz
Tweeter Single 1"
Woofer Dual 5.25"
Dimensions H W D (inches) 7.5x17 x7.5
Dimensions H W D (mm) 191 x 432 191
Weight (lbs) each 14.1 lbs

BRYSTON



**MOUNTING
BRACKETS FOR
ONWALL**

**WELCOME
TO THE
NEXT LEVEL**

BRYSTON ONWALL / INWALL SPEAKERS

TOW ON-WALL



ON-WALL SPECIFICATIONS

Enclosure Reflex / Vortex
Max RMS Wattage 300 Watts
Min Amp Power 10 Watts
Freq Resp +/-3dB 60 Hz- 20 kHz
Impedance (Ohms) 8
SPL in Room 1w/1m (dB) 91 dB
SPL Anechoic 1w/1m (dB) 87 dB
X-Over 250 Hz & 2.4 kHz
Tweeter Single 1" Titanium
Midrange Single 3"
Woofer Single 6.5"
Dim HWD (inches) 15.5x8.5x8.25
Dim HWD (cm) 48x23x26
Weight (lbs) each 11
Weight (kg) each 5

IN-CEILING SPECIFICATIONS

Acoustic Suspension
Max Power: 250 Watts
Min Amp Power: 10 Watts
FR +/-3dB: 120 - 22 kHz
+3dB- 9dB: 90 - 22 kHz
Impedance 8 Ohms
SPL in Room 1w/1m: 92 dB
Anechoic 1w/1m: 88 dB
Crossover 2.2 kHz
Tweeter: Single 1" titanium
Woofer: Single 6.5" aluminum
On-ceiling Dimension (inches) 9 5/8" diameter x 3/8"
In-ceiling (Cut out) Dim (inches) 8 1/4" diameter x 4 9/16"
On-ceiling Dimensions (mm) 244 diameter x 9
In-ceiling (Cut out) Dimensions (mm) 210 diameter x 116
Weight (lbs) each 12.7 lbs
Weight (kg) each 5.76 kg

TIW IN-WALL



IN-WALL SPECIFICATIONS

Acoustic Suspension
Max RMS Wattage 300 Watts
Min Amp Power 10 Watts
Freq Resp +/-3dB 60 Hz- 20 kHz
Impedance (Ohms) 8
SPL in Room 1w/1m (dB) 91 dB
SPL Anechoic 1w/1m (dB) 87 dB
X-Over 250 Hz & 2.4 kHz
Tweeter Single 1" Titanium
Midrange Single 3"
Woofer Single 6.5"
Dimensions HWD (inches)
15.5x8.5x8.25
Dimensions HWD (cm)
48x23x26
Weight (lbs) each 11
Weight (kg) each 5

TIC



BRYSTON




**ALL BRYSTON
SPEAKERS COME
WITH FOUR
CHANGEABLE
MODULES TO
SWITCH BETWEEN
SINGLE-AMP
BI-AMP
TRI-AMP
ACTIVE**



ALL BRYSTON SPEAKERS AVAILABLE IN ACTIVE OR PASSIVE VERSIONS

Not only are all our Bryston speakers available in **ACTIVE** or **PASSIVE** versions but any passive version can be easily modified to an active version simply by changing out the Passive **crossover module** for the Active.




BYSTON



IT'S
IMPORTANT
TO
STAY
ACTIVE

WELCOME
TO THE
NEXT LEVEL

BYSTON 'ACTIVE' T¹⁰



Why Active

Bryston's 'Active' speakers come even closer to the ideal power response without sacrifices to the on-axis response

Power response is the weighted measure of a loudspeaker's total energy. It is not sufficient to simply design for flat on-axis response.

By ensuring that power response tracks the more narrowly defined listening window closely, we can ensure that the room's contribution to the final sound is beneficial, not destructive.

Bryston's Active Loudspeakers leverage the incredible power of our DSP engine to enable our engineers to optimize both listening window and sound power at once. These are often competing ideals. Now listeners can have truly neutral in-room response across the whole spectrum.

Select your Speakers

Bryston offers all our T-10 models of speakers in Active versions. Each loudspeaker is expertly constructed in Canada and finished by talented craftsmen in the fine wood of your choosing. No 'internal crossover' is present, Each driver section is powered directly from the attached amplifier.

Whichever you pick, expect realistic tone, lifelike three dimensional space, and incredible clarity. All models are protected by Bryston's legendary 20 year warranty.

Pick your Power

Unlike with so many other active loudspeaker systems, with our models amplification is more than simply an afterthought. Each loudspeaker requires three amplifier channels - one for high frequency, one for midrange, and one for low frequency. Any mixture of Bryston power amplifiers would be the optimum choice or, build your own amplifier complement as long as the gains are the same.

The Crossover

Inside the all new BAX-2 DSP Crossover lies the magic that elevates the system to a new ultimate performance. The BAX-2 receives line level analog audio from your preamp and converts it to digital with exacting precision. Like a traditional crossover, bands are divided, but response is also corrected. Our engineers use the powerful DSP engine to precisely neutralize system response errors that would otherwise go uncorrected. Low, midrange, and high frequency outputs are generated which then feed 6 amplifier channels.

Do you want a custom sound? You can even custom tailor the bass response (typically an issue in small rooms) to match your room using the on-board web based user interface.


BYSTON



ALL BRYSTON
SPEAKERS ARE
AVAILABLE IN
ACTIVE
OR
PASSIVE
VERSIONS



BRYSTON BAX-2 ACTIVE CROSSOVER



The Bryston BAX-2 Digital Electronic Crossover is really a very specialized and unique crossover.


Unless designed as a dedicated crossover all active crossovers typically provide the customer with a more typical 'generic' approach to adjustments.

By that I mean you can choose the slope, the crossover point and sometimes the Q but they do not take into account the unique total radiated energy of the speaker (which is exactly what you hear in a real room)

The Bryston BAX-2 on the other hand is designed in the Bryston factory anechoic chamber with over 300 measurements both vertically and horizontally with a specific Bryston speaker in mind.

Anechoic chambers are very expensive but they eliminate any reflections from the speaker influencing the measurement of 'on and off' axis sound power response accuracy.

Each and every Bryston Active Model T-10 loudspeaker has a different and dedicated version of software depending on the specific speaker model.



BRYSTON



ACTIVE FEATURES

- XLR analog input from your line-level preamp.
- 3 pairs (low, mid, high) of XLR analog out to feed your choice of amplifier complement
- 96/24 analog to digital to analog conversion
- Factory programmed crossover settings
- Controllable via web user interface
- 6 channels of amplification required (3 channels per loudspeaker)
- Firmware upgradeable (e.g. w/ Bass EQ and other new features)

TYPICAL BRYSTON 'ACTIVE' SETUP


Unless designed as a dedicated crossover most universal active crossovers just provide the customer with a 'generic' approach to adjustments. By that I mean you can choose the slope and the crossover point and sometimes the 'Q' but they do not take into account the 'SOUND POWER' or total radiated energy of the speaker (which is what you actually hear in a room)

The Bryston BAX-2 on the other hand is designed with a specific Bryston speaker in mind. The Active Model T¹⁰'s have different software than the Middle T¹⁰ and the Mini T¹⁰ has different software again. The reason for that is we put each version of the Model T¹⁰'s in our factory anechoic chamber and we make over 300 measurements but vertically and horizontally around the speaker and adjust the software to provide as accurate as possible the best SOUND POWER for the specific Model T¹⁰ speaker.

Additionally, most fully active systems restrict your choice of preamplifier and amplifiers by building in internal chip type amplifiers and preamplifiers which save space but can limit performance.

Bryston's system includes a high resolution external digital crossover model BAX-2 that accepts input from your favorite stereo analog preamplifier and outputs analog signal to your choice of amplifiers. The BAX-2 makes it easy to choose the amplifiers that work best for your listening preferences. Each loudspeaker needs 3 (preferably Bryston) amplifier channels with equal gain.

Most listeners will choose a high powered mono amp for the bass section and a medium powered two channel amp for the midrange and tweeter sections. High quality DSP crossover improves performance by directly powering drivers without intermediate passive components in the crossover. Also, much finer adjustments can be made to compensate for response non-linearities. Because we are no longer confined to traditional crossover geometry, we can tailor the 'on and off axis' response independently for incredibly natural tone and spatial resolution.



BRYSTON

Model T Active Loudspeaker System

BRYSTON



ALL BRYSTON
SPEAKERS ARE
AVAILABLE IN
ACTIVE
OR
PASSIVE
VERSIONS



SUBWOOFER INTEGRATION

SUBWOOFER integration has always been difficult to achieve given the complexity of the many different types of Main speakers utilized in a typical audio system.

Bryston is pleased to introduce a series of Bass Towers specifically designed to integrate with our T-10 Series Tower Speakers. These stereo Bass Towers can be used with either our '**Passive or Active**' T-10 Tower speakers.

There will be three physically, cosmetically and software matched versions of these TS-10 Sub Towers:

1. **Model TS-10 Bass Tower (Six - 8 inch drivers each)**
2. **Middle TS-10 Bass Tower (Six - 6.5 inch drivers each)**
3. **Trim TS-10 Bass Tower (Four - 6.5 inch drivers each)**
4. **Compact TS-10 Bass Tower Sub (Two-8 inch drivers each)**

The TS-10 stereo subwoofer towers will require the new Bryston BAX2 (2-way electronic crossover) and two more channels of amplification with dedicated software which utilizing DSP will blend the TS-10 Tower to the Mains over the bass frequency range response from 150Hz down to their specific cutoff point.

At very low frequencies you will have the stereo TS-10 Bass Tower and the bass drivers in the stereo T-10 Mains all integrated and acting as one massive integrated bass driver.

BAX-2 ELECTRONIC CROSSOVER



TS-10 SUB TOWER



This is the optimum way to achieve the proper integration of your Main speakers with your Subs.

It will also drive the room in the bass area from multiple points in space which helps reduce the standing waves in your listening room as well as incredibly low distortion throughout the very low bass frequencies due to multiple low frequency drivers sharing the load.

BB
BRYSTON



INTELLIGENT

DSP

ENSURES

ULTIMATE

PERFORMANCE

BASS TOWER SPECIFICATIONS

DSP TECHNOLOGY

All the Bryston TS-10 Bass Towers utilize the Bryston BAX-2 digital electronic crossover with intelligent DSP to ensure optimize performance.

The TS-10's have a perfectly linear response down to their specific cutoff point. This gives you bass realism, texture and control like you have never experienced before.

The intelligent DSP also means your TS-10 Bass Tower plays at very powerful levels without ever having to worry about unwanted pops and noises coming from your subwoofer.

TS-10 BASS TOWERS

Model TS-10 Bass Tower (Six - 8 inch drivers each)

- Matches Physically and Cosmetically the Model T-10 Tower
- Dimensions H W D (inches) 72" x 12" x 17"
- Dimensions H W D (mm) 1830 x 310 x 440
- Frequency Response (+/-3dB) Hz 16 - 150

MiddleTS-10 Bass Tower (Six - 6.5 inch drivers each)

- Matches Physically and Cosmetically the Middle T-10
- Tower Dimensions H W D (inches) 67" x 10" x 17"
- Dimensions H W D (mm) 1700 x 440 x 260
- Frequency Response (+/-3dB) Hz 18 - 150

TrimTS-10 Bass Tower (Four - 6.5 inch drivers each)

- Matches Physically and Cosmetically the Trim T-10 Tower
- Dimensions H W D (inches) 60" x 10" x 16"
- Dimensions H W D (mm) 1520 x 260 x 410
- Frequency Response (+/-3dB) Hz 18 - 150

FEATURES

- Ultra Hi-Powered Woofer Design
- Enclosure - Sealed
- Die Cast Woofer Basket
- DSP Amplitude Response Control
- Featuring XLF (Extended Low Frequency) Intelligent Control



BRYSTON



**ALL BRYSTON
SPEAKERS ARE
AVAILABLE IN
ACTIVE
OR
PASSIVE
VERSIONS**

**WELCOME
TO THE
NEXT LEVEL**

BRYSTON WIRELESS SPEAKERS

Our Bryston Wireless loudspeakers are based on Bryston's passive speakers using the high quality internal passive crossovers and drivers but the Wireless speaker series models incorporate an internal state of the art amplifier in each speaker.

All Wireless models ship with a Wireless 'four-in-one transmitter' that permits streaming over Wi-Fi via Apple AirPlay or UPnP.

On the rear of the transmitter are a line-level analog input, digital optical in, four USB ports for connecting external storage devices, and an Ethernet port.

It also incorporates a Pi Linux-based computer, which makes possible network playback from NAS drives and supported streaming services, under control of a Web-based interface that can run on iOS and Android devices.



BRYSTON



**ALL BRYSTON
SPEAKERS
ARE AVAILABLE
IN CUSTOM
COLOURS
AND
FINISHES**

STANDARD AND CUSTOM COLOURS


You can order your Bryston Model T¹⁰ loudspeaker finished in our beautifully lacquered fine hardwood in the standard stock colours or a custom finish of your choosing to complement your home décor.

In addition to the in-stock Walnut, Boston Cherry, and Black Ash shown below, a larger selection of natural wood and highly durable painted veneers can be selected for any Bryston freestanding or stand-mounted loudspeaker.


Natural Cherry



Boston Cherry




Black Ash



Red Rosewood



Walnut



Your Custom
Finish

**BRYSTON SPEAKERS HAVE A 10 YEAR WARRANTY
TO THE ORIGINAL OWNER**

WWW.BRYSTON.COM



Contact Information



HEAD OFFICE

2885 Highway 60
Dwight, Ontario
Canada
POA 1H0

PHONE NUMBER CANADA

1 800 632 8217

WARRANTY

Canadian Customers:
Bryston Ltd
2885 ON-60
Dwight ON
POA 1H0

USA Customers:
Bryston Ltd
600 Main St.
Tonawanda NY
14150



WEBSITE

www.bryston.com

2026